# EASYGATE ELITE

STYLISH. DISCREET. FLEXIBLE.

## Entrance Control





#### AT A GLANCE

- Available in rounded cabin
- Barrier opening time from 0.7 seconds
- Customisable finishes
- DDA Compliant

#### [70.87"] 1800 ХDМ [39"] <u>160</u> [6.3"] 066 132 [5.2"] 6 1240 [48.8"] 0 0 DDA/ADA 0 Standard Standard 550 [21.7"] 650 [25.6"] 920 [36.2"] Max 600 [23.6"] Max 1100 [43.3"] Max 1000 [39.4"] 0 0 0 1240 [48.8"] 0 0 DDA/ADA 0 Standard Standard 550 [21.7 920 [36.2" 650 [25.6" 600 [23.6"] 1100 [43.3"] 1000 [39.4"]

### **SPECIFICATIONS**

#### DIMENSIONS

Standard:	1240mm(L) x 132mm(W) x 990mm(H)
Barrier Height:	990mm – 1800mm
Lane width:	550mm – 1100mm (customisable)
Gap Between barriers:	50mm
MBTF:	3,000,000 operations
Warranty:	24 months
Sensors:	Up to 26 sensor pairs
Power Supply Input:	230 volts
Control Electronics:	12 V DC
Current:	Standby 0.4 A
Consumption:	Operational 6 A
Consumption:	Operational 6 A

Operating Temp:	10°C to 50°C (with heater)
Motor:	12 V DC
Operation Mode:	Normally Closed
Control:	Card In / Card Out Card In / No Exit Card In / Free Exit Locked Free Passage
Pictograms:	Wait Mode (White Indicator) Access Granted (Green Indicator) Illegal Transaction (Red Indicator)
Barrier Opening Time (Standard lane):	0.7 Seconds
PIATENIALS	
Ton Cover:	8mm Smalled Glass (other entions)
Top Cover:	8mm Smoked Glass (other options)
Top Cover: Front Cover:	8mm Smoked Glass (other options) Black RAL
•	

Specifications subject to change without prior notice.

For Remote Turnstile Maintenance access to the sites network is required and the service is subject to a support agreement